



Technical Data MEDIUM COLLECTION

Luxury, high performance PVC-floor covering for high commercial and heavy duty residential applications.

Covering type in accordance with EN 649	Heterogeneous Plank Wood	Heterogeneous Tiles
Number of colours	57	27
Pack. Unit/Pallet	3.34 m ² /200.40 m ²	3.34 m ² /200.40 m ²
Performance classification EN 685	23, 33, 42	23, 33, 42
Total thickness EN 428	2.5 mm	2.5 mm
Wear layer thickness EN 429	0.55 mm	0.55 mm
Surface treatment	yes/PU	yes/PU
Bevelled edges	depending on design	depending on design
Total weight EN 430	4.08 kg/m ²	4.08 kg/m ²
Residual indentation EN 433	0.05 mm	0.05 mm
Castor chair suitability EN 425	suitable for castor chairs in acc. with EN 12529, type W	suitable for castor chairs in acc. with EN 12529, type W
Underfloor heating	suitable (up to 28°C)	suitable (up to 28°C)
Behaviour to fire EN 13501-1	Bfl-s1	Bfl-s1
Resistance to thermal conductivity DIN 52612	0.02 m ² K/W	0.02 m ² K/W
Impact sound improvement EN 140-8	4dB	4dB
Colour fastness EN ISO 105-B02	> 6	> 6
Electrostatic characteristics EN 1081	> 10 ¹⁰	> 10 ¹⁰
Chemical resistance EN 423	conforms*	conforms*
Slip resistance	R9	R9
Adhesive recommendation	see installation instruction	see installation instruction
Maintenance/Cleaning recommendation	CC-Dr. Schutz	CC-Dr. Schutz

*Vis-à-vis the short-term effects of normal, domestic agents.

Please also note the installation and cleaning and care instructions. (Date: 01/09/2012)

